

BIOGUARD ACOUSTIC

Highly suitable for medical applications, bioguard acoustic combines superior acoustical qualities helping to balance room acoustics, whilst containing fungicides and biocides, which actively combat harmful fungi, mould & mildew, yeasts and bacteria.

Durability	Relative Installed Cost	Performance
	<div style="display: flex; justify-content: space-around;"> \$ \$\$ \$\$\$ \$\$\$\$ </div>	

http://www.armstrong-aust.com.au/commclgpac/en-au/ceilings.asp/mineral-fibre/bioguard-acoustic/_/N-1z141t5Z1z141xr

DUNE

Cost effective ceiling tiles with a fine textured finish. A contemporary upgrade at a modest price. Nondirectional visual assists in reducing installation times and minimises waste, whilst ensuring good sound absorption.

Durability	Relative Installed Cost	Performance
	<div style="display: flex; justify-content: space-around;"> \$ \$\$ \$\$\$ \$\$\$\$ </div>	

http://www.armstrong-aust.com.au/commclgpac/en-au/ceilings.asp/mineral-fibre/dune/_/N-1z141t5Z1z141yn

DUNE MAX


With an NRC rating of 0.70 the Dune Max is a great product for a high acoustical application. Its fine texture surface ensures a modern finish as well as assisting in energy efficiency due to its light reflectance properties.

Durability	Relative Installed Cost	Performance
	<div style="display: flex; justify-content: space-around;"> \$ \$\$ \$\$\$ \$\$\$\$ </div>	

http://www.armstrong-aust.com.au/commclgpac/en-au/ceilings.asp/mineral-fibre/dune-max/_/N-1z141t5Z1z141y0

DUNE SECOND LOOK

Nondirectional ensures efficient installation and minimises waste.
Good sound absorption, scratch resistance and high light reflectance.

Durability	Relative Installed Cost	Performance
	<div style="display: flex; justify-content: space-around;"> \$ \$\$ \$\$\$ \$\$\$\$ </div>	

http://www.armstrong-aust.com.au/commclgpac/en-au/ceilings.asp/mineral-fibre/dune-second-look/_/N-1z141t5Z1z141yb

FINE FISSURED



NRC rating of 0.55 ensures excellent sound absorption.
Non directional reduces waste and installation time

Durability	Relative Installed Cost	Performance
	<div style="display: flex; gap: 10px;"> <div style="background-color: #76b82a; color: white; padding: 2px 10px;">\$</div> <div style="background-color: #76b82a; color: white; padding: 2px 10px;">\$\$</div> <div style="background-color: #a6a6a6; color: white; padding: 2px 10px;">\$\$\$</div> <div style="background-color: #a6a6a6; color: white; padding: 2px 10px;">\$\$\$\$</div> </div>	

http://www.armstrong-aust.com.au/commclgpac/en-au/ceilings.asp/mineral-fibre/fine-fissured/_/N-1z141t5Z1z141ym

FINE FISSURED CERMAGUARD

The totally inorganic properties of this product ensure it is washable, scrubbable, and resistant to the growth of mould and bacteria. 20 year limited system warranty available on this product. Properties also include resistance to chemical fumes.
The non directional visual reduces installation time and waste.

Durability	Relative Installed Cost	Performance
	<div style="display: flex; gap: 10px;"> <div style="background-color: #a6a6a6; color: white; padding: 2px 10px;">\$</div> <div style="background-color: #a6a6a6; color: white; padding: 2px 10px;">\$\$</div> <div style="background-color: #76b82a; color: white; padding: 2px 10px;">\$\$\$</div> <div style="background-color: #a6a6a6; color: white; padding: 2px 10px;">\$\$\$\$</div> </div>	

http://www.armstrong-aust.com.au/commclgpac/en-au/ceilings.asp/mineral-fibre/fine-fissured-ceramaguard/_/N-1z141t5Z1z141yl

FINE FISSURED HIGH NRC / HIGH CAC

NRC rating of 0.70 prevents airborne sound intrusion between rooms. Extremely high CAC rating of 35-40 means this product is ideal for environments with temperatures up to 49C and high humidity up to 99%.

Durability	Relative Installed Cost	Performance
	<div style="display: flex; gap: 10px;"> <div style="background-color: #76b82a; color: white; padding: 2px 10px;">\$</div> <div style="background-color: #a6a6a6; color: white; padding: 2px 10px;">\$\$</div> <div style="background-color: #a6a6a6; color: white; padding: 2px 10px;">\$\$\$</div> <div style="background-color: #a6a6a6; color: white; padding: 2px 10px;">\$\$\$\$</div> </div>	

http://www.armstrong-aust.com.au/commclgpac/en-au/ceilings.asp/mineral-fibre/fine-fissured-high-nrchigh-cac/_/N-1z141t5Z1z141xz

FINE FISSURED SECOND LOOK

Four geometric scored visuals mean this tile is XXXXX.
The non direction visual reduces installation time and wastage.

Durability	Relative Installed Cost	Performance
	<div style="display: flex; gap: 10px;"> <div style="background-color: #a6a6a6; color: white; padding: 2px 10px;">\$</div> <div style="background-color: #76b82a; color: white; padding: 2px 10px;">\$\$</div> <div style="background-color: #a6a6a6; color: white; padding: 2px 10px;">\$\$\$</div> <div style="background-color: #a6a6a6; color: white; padding: 2px 10px;">\$\$\$\$</div> </div>	

http://www.armstrong-aust.com.au/commclgpac/en-au/ceilings.asp/mineral-fibre/fine-fissured-second-look/_/N-1z141t5Z1z141yk

MINATUFF


Highly durable the Minatuff range is impact resistant.
The non directional visual reduces installation time and wastage.

Durability	Relative Installed Cost	Performance
	<div style="display: flex; justify-content: space-around; align-items: center;"> \$ \$\$ \$\$\$ \$\$\$\$ </div>	 

http://www.armstrong-aust.com.au/commlgpac/en-au/ceilings.asp/mineral-fibre/minatuff/_/N-1z141t5Z1z141yw

ULTIMA

The totally inorganic properties of this product ensure it is washable, scrubbable, and resistant to the growth of mould and bacteria. 20 year limited system warranty available on this product. Properties also include resistance to chemical fumes.
The non directional visual reduces installation time and waste.

Durability	Relative Installed Cost	Performance
   	<div style="display: flex; justify-content: space-around; align-items: center;"> \$ \$\$ \$\$\$ \$\$\$\$ </div>	  

http://www.armstrong-aust.com.au/commlgpac/en-au/ceilings.asp/mineral-fibre/ultima/_/N-1z141t5Z1z141ye

SYMBOL	DESCRIPTION
	<p><u>Scratch Resistance</u> Excellent resistance to surface scratching, scuffing or chipping based on Hess Rake test.</p>
	<p><u>Soil Resistance</u> Excellent resistance to dirt and/or grease, some products meet acceptance criteria like USDA and/or Class 100 Clean Room.</p>
	<p><u>Washability</u> Offers superior wash resistance without compromising panel finish integrity, using a washability tester as per ASTM D 4828</p>
	<p><u>Scrubability</u> Withstands up to 150 scrub cycles using a scrubability tester as per ASTM D 2486.</p>
	<p><u>Impact Resistance</u> Excellent resistance to surface impact based on Falling Ball test – Modified ASTM D 1037</p>
	<p><u>High Acoustics</u> Product has NRC (Noise Reduction Coefficient) of 0.65 or greater and/or AC (Articulation Class) of 170 or greater.</p>
	<p><u>HumiGuard Plus</u> Superior sag resistance, recommended for areas subject to high humidity, up to standing water and outdoor applications.</p>
	<p><u>High Light Reflectance</u> Light reflectance of 0.83 or greater.</p>
	<p><u>Fire Resistance</u> Available in fire-resistive options (Fire Guard), tested in specific UL floor/ceiling or roof/ceiling construction design assemblies.</p>