



PEAKFORM SUSPENSION SYSTEMS

Inspiring Great Spaces™

Armstrong®

CEILING SYSTEMS

THE PEAKFORM RANGE: WHERE INNOVATION MEETS PERFORMANCE



PeakForm is a comprehensive range of suspended ceiling grid solutions designed to meet most commercial design requirements:

- General Application: Including PRELUDE XL² 24mm and SUPRAFINE XL² 15mm Tee Grid systems.
- Designer Applications: Including the minimalist SILHOUETTE 15 XL² Steel Exposed Slotted Grid.

Axiom Perimeter Solutions

PeakForm Grid Systems are made complete with a Comprehensive range of Axiom Perimeter Solutions, including: Wall angles, Trims, Transitions, Pelmet and Accessories.

PeakForm Grid Profiles

PeakForm is an innovative design for Main Bars and Cross Runners. The taller **PeakForm** profiles are engineered to create a stronger, more stable suspension system making installation both faster and easier.

PeakForm Main Bars feature a firm, quick and easy assembled Main Bar to Main Bar / bulb to-bulb connection.

The staked-on Superlock joiner clip allows for Main Bars to be disconnected and reconnected laterally in low clearance areas or in the middle of a room. Superlock is an industry first staked-on clip for Main Bars which provide tighter, secure bulb-to-bulb connections; connections are confirmed by an audible click.



Thin gauge technology:

A lighter carton weight enables easier handling on site, plus the added benefit of the **PeakForm** bulb allows easy cutting of the grid.



Physical detail

All grid sections are made from double-web galvanised steel with a surface finish of baked polyester paint.

Rotary Stitched for strength



All **PeakForm** components feature a unique “rotary stitched” construction. The two metal layers of the vertical web are mechanically locked together in a sophisticated in-line process. Stitching enhances the torsional resistance and general “feel” of the **PeakForm** components.



PeakForm “click” installation

PeakForm Cross Runners in both 24mm and 15mm widths feature an advanced stab system that locates with an audible “click”, ensuring a solid installation at all times. The “stab” end details are precision stamped from a separate piece of high grade steel providing increased accuracy and speed of installation.

Cross Runners are inserted to the right of each other through the Main Bar slots and easily pushed home.



Sustainability

Armstrong **PeakForm** suspension systems contain 25% recycled content and can be fully recycled at the end of life.


PeakForm grid systems are modular and can be disassembled and reused.

PeakForm suspension systems meet the requirements of Australian Standard 2785-2000 “Suspended Ceilings Design and Installation” and are designed for use with a wide variety of Armstrong ceiling products including: mineral and soft fibre, metal, wood and special solutions.

Compliant with Australian & New Zealand Standards


PeakForm suspension systems meet the requirements of AS/NZS 2785-2000 “Suspended Ceilings Design and Installation” and are designed for use with a wide variety of Armstrong ceiling products including: mineral and soft fibre, metal, wood, plasterboard and other special panels.

PEAKFORM SILHOUETTE 15 XL²




PEAKFORM SILHOUETTE 15 XL² Steel Exposed Slotted Grid is designed to create a crisp, clean look in conjunction with Tegular B15 tiles to provide an enhanced aesthetic.

Main Bar: SILHOUETTE 15 XL²



Item Number	Dimensions			Rout Centres mm	Content / Carton		Weight / Carton kg
	length (mm)	height (mm)	width (mm)		pcs	lm	
with 6mm reveal							
HBP 80 40 82	3600	45	15	600	20	72	24.50

Cross Runners: SILHOUETTE 15 XL²




Item Number	Dimensions			Rout Centres mm	Content / Carton		Weight / Carton kg
	length (mm)	height (mm)	width (mm)		pcs	lm	
with 6mm reveal							
HBP 80 30 82	1200	45	15	600	60	72	24.50
HBP 80 20 82	600	45	15	—	60	36	12.70

* Note: Item mitred on one side only


Section Drawings (Standard Items for 600x600 module configuration)




Main Bar SILHOUETTE 15



Cross Runner SILHOUETTE 15 XL²




Cross Runner SILHOUETTE 15 XL²




PERIMETER TRIMS AND ACCESSORIES

Perimeter Trims


Item Number	Description	Length (mm)	Content / Carton pcs / lm	Weight / Carton kg
HBPT1932H HBP784003	Steel Perimeter Trims: Roll Formed and Prepainted			
	Long Leg Wall Angle	3600	30	21
	Shadow Line Wall Angle	3600	30	20
AL008RCPGW AL009RCPGW ALBULK3600GW	Aluminium Perimeter Trims: Extruded and Powdercoated			
	Wall Angle for Roll In Clip Attachment	3600	20	14
	Shadow Line Wall Angle for Roll In Clip Attachment	3600	20	14
	Bulkhead Trim (suits both 10mm and 13mm Pb)	3600	6	6




Steel




HBPT1932H




Steel




HBP 784003




Aluminium




AL008RCPGW




Aluminium



AL009RCPGW




Aluminium




ALBULK3600GW

Suspension & Accessories



BPDW10LTG90
BPDW13LTG90
BPDW16LTG90



ALRIC




ARM-051




SCPF




Trclip and threaded rod/nut




DWDFC



DWDFC120



BPUHDCA



BPDLC



274



188




247



TOUCH UP
PAINT



254




HBPGM1249


Item Number	Description	Dimensions length (mm)	Content / Carton pcs	Weight / Carton kg
SCPF	Hook Suspension Clip for 5mm Rod	165	100	2.2
ARM-051	Direct Fix Clip	175	100	2.6
Trclip	Suspension Clip for 6mm Threaded Rod	80	100	2.0
M6 Rod	6mm Threaded Rod	1200	50	11.0
M6 Nuts	6mm nuts for Threaded Rod	—	200	0.4
BPDLC	Direct Load Ceiling Clip	80	250	5.5
BPUHDCA	Universal Hold Down Clip	—	1000	4.0
ALRIC	Roll In Clip	65	100	5.0
ROD 5mm	5mm Suspension Rod	4000	40	24.2
SR2536	2.5mm Suspension Wire	3600	160	25.0
188	Angle Bracket	47 x 47	100	1.2
247	Suspension Rod Angle Bracket	55	100	2.1
274	Suspension Rod Bracket	80	100	2.1
254	5mm ROD joiner spring adjustable	—	100	0.9
HBPGM1249	Expansion Sleeve to suite 24mm grid	100	100	5.0
BPDW10LTG90	Drywall Transition Clip suits 10mm Plasterboard	—	200	11.0
BPDW13LTG90	Drywall Transition Clip suits 13mm Plasterboard	—	200	11.0
BPDW16LTG90	Drywall Transition Clip suits 16mm Plasterboard	—	200	11.0
GPGW	Grid Touch Up Paint (128g net)	—	6	1.3
DWDFC120	120mm L Shape	120	100	5.0
DWDFC	180mm L Shape	180	100	6.5

Perimeter Detailing Recommendations


Square Edge Panels






Grid, Wall Angle and "Square Edge Panel" at same level



Grid, Wall Angle and "Square Edge Panel" at same level




Tee Bar is secured to Wall Angle via Roll In Clip




Note: Wall Angles should be fixed to wall at 450mm centres


Tegular Edge Panels





Panel edge is field "tegulated" at Wall Angle



Wall Angle position is dropped to level of face of Panel; Tee Grid is packed at Wall Angle and Panel is square cut at wall angle



Panel edge is field "tegulated" at Wall Angle



Wall Angle position is dropped to level of face of Panel; Tee Grid is packed at Wall Angle and Panel is square cut at wall angle

For information on Blue Tongue Aluminium Grid and Axiom Perimeter / Pelmet systems, refer to the following brochures.



SPECIFICATIONS

Scope

The contractor to furnish all materials, labour and equipment for the erection of the exposed ceiling system where so indicated on the architectural drawings.

Material

Ceiling suspension shall be Armstrong PeakForm two way exposed, hot dipped galvanised steel system; (either): Prelude XL² 24mm Tee, SupraFine XL² 15mm Tee, or Silhouette XL² 15mm Steel Exposed Slotted "shadowline hat" profiles. All materials supplied by Armstrong meet the requirements of Australian Standard 2785-2000 "Suspended Ceilings Design and Installation".

Perimeter Detail

Wall Angles should be fixed to wall at 450mm centres. Exposed ceiling grid members intersecting with the Wall Angle or Shadowline Wall Angle, may either be unfixed, or fastened with a Roll In Clip.

Installation

The Main Bar shall be hung with a 5mm galvanised rod and clip system or 2.5mm wire, accurately levelled. Suspension points shall be spaced at 1200mm* centres along the Main Bar. Cross Runners shall intersect and be positively locked to Main Bars. Panel Hold Down Clips to be used as required. Hangers, Main

Bars and Cross Runner shall be spaced so as not to exceed the design ceiling load or as may otherwise be required to prevent deflection in excess of 1/360 of the span of the spacers or Main Bars. Where light fittings, air conditioning fixtures etc are to be supported by the grid system, extra hangers may be required. Down bracing to be incorporated in ceiling systems when used externally or adjacent to opening prone to sudden uplift caused by external wind forces.

* For suspension points greater than 1200mm centres along the Main Bar, contact your local Armstrong representative for load ratings.

Maximum Fixture Weight

		Main Bar to Main Bar (Fixture / Panel Orientation)			
Main Bar	—				
Cross Runner x 600	—				
Cross Runner x 1200	—				
1. FIXTURE* (mm)		1200 x 600	600 x 600	1200 x 300	600 x 600
2. PLANNING MODULE (mm)		1200 x 1200	1200 x 1200	1200 x 600	1200 x 600
3. HANGER SPACING (mm)		1200	1200	1200	1200
Max Fixture Weight (kgs)					
4. PRELUDE 24		21.2 kg	14.0 kg	17.4 kg	14.0 kg
5. SUPRAFINE 15		27.9 kg	13.9 kg	24.9 kg	13.9 kg
6. SILHOUETTE 15		-	-	-	14.2 kg
		Cross Runner to Cross Runner (Fixture / Panel Orientation)			
Main Bar	—				
Cross Runner x 600	—				
Cross Runner x 1200	—				
1. FIXTURE* (mm)		1200 x 600	600 x 600	600 x 600	1200 x 300
2. PLANNING MODULE (mm)		1200 x 1200	1200 x 1200	600 x 600	1200 x 1200
3. HANGER SPACING (mm)		1200	1200	1200	1200
Max Fixture Weight (kgs)					
4. PRELUDE 24		10.6 kg	10.6 kg	37.5 kg	17.4 kg
5. SUPRAFINE 15		-	-	37.3 kg	-
6. SILHOUETTE 15		-	-	37.9 kg	-

Connection Strength (SEISMIC)

Main Bar

HBP734042

Minimum KGS to Pull Out Compression / Tension

174 kg / 133 kg

Cross Runner

All Cross Runners exceed 136 kg in both compression / tension.

Loading Parameters

- Main Bars at 1200mm centres
- Cross Runners 1200mm at 600mm spacing
- Suspension points spaced at 1200mm on Main Bar

*Note: Additional independent support of heavy fixtures should be considered for safety purposes.

The above data is based on 1200mm hanger spacing, board weight of 4.8kg/m², maximum deflection of tees not to exceed 1/360 of the span and suspension system installed in accordance with AS2785-2000.



SCAN* THIS CODE to learn more about our PeakForm Suspension Systems

*Download a Free QR code reader app available from Apple store

Armstrong, the Global Leader in Acoustic Ceiling Systems
www.armstrongceilings.com.au

NSW

Armstrong World Industries Pty. Ltd.
 99 Derby Street,
 Silverwater NSW 2128
 Telephone: (02) 9748 1588

VIC/TAS

Armstrong World Industries Pty. Ltd.
 Unit 1, 88 Henderson Road,
 Rowville VIC 3178
 Telephone: (03) 8706 4000

QLD/NT

Armstrong World Industries Pty. Ltd.
 6 Barrinia Street,
 Slacks Creek QLD 4127
 Telephone: (07) 3809 5565